

## H5S5.2.27.HC Padlock, shackle 15/27 mm, with RTC

---

### System-level description

iLOQ S5 locking system offers advanced security and convenient access management for master-key locking environments.

The iLOQ S5 padlocks enable usage of the iLOQ S5 locking system for securing remote objects and locations. The self-powered iLOQ padlocks are available in different body and shackle sizes. The iLOQ padlock records audit trails of key usage and enables flexible access management for each key and each padlock. The security level is kept high and security gaps caused by lost keys can be eliminated completely without costly changes of locks and keys. The iLOQ D2D network allows users to update lock-related access rights, time limitations and lists of lost keys as well as collect log event data from the locks.


The product should not be modified in any way except in accordance with those modifications described in the instructions.

---

### Feature summary

- Programmable electromechanic padlock for iLOQ S5 locking system
- Self-powered: no batteries or external energy source required for the lock and key
- Lock acts as a part of the iLOQ D2D network
- All iLOQ S5 padlocks and iLOQ S5 keys are mechanically identical
- Secured using powerful encryption methods: 256-bit AES (Advanced Encryption Standard)
- Programmed using a PC and the iLOQ P55.1 Programming Key
- Blocklist for individual lost keys
- Access group list for key accesses
- Firmware updateable

## Dimensional drawing



## Memory capacity

|                                  |     |
|----------------------------------|-----|
| Number of access rights .....    | 210 |
| Number of blocklisted keys ..... | 500 |
| Number of time slots .....       | 10  |
| Size of event log .....          | 500 |

## Technical data

|   |                              |
|---|------------------------------|
| Chain included .....                              | <b>X</b>                     |
| Ingress protection rating .....                   | IP21                         |
| Security grade .....                              | Grade 5                      |
| Real time clock battery lifetime .....            | 10 years                     |
| Real time clock compatibility .....               | One real time clock included |
| Remote management with iLOQ Online products ..... | <b>X</b>                     |
| Surface treatment .....                           | Polished chrome              |
| Maximum temperature .....                         | 80°C                         |
| Minimum temperature .....                         | -20°C                        |
| Usage environment .....                           | Outdoor                      |